

# FHDRM

## 1080p FULL HIGH DEFINITION RUGGED MONITOR SERIES

Built with a Full HD 1920x1080 LCD, the FHDRM Display Series deliver a MIL-Spec design with low-power consumption, high brightness backlight, and an ultra-thin form factor for critical operations requiring 1080p detail. The rugged FHDRM monitor ensures complete optical performance and full reliability while providing a small footprint for constrained spaces. Programmable bezel soft keys allow full control of external systems or a custom interface of internal display features (video processing, picture layout, user interface preferences, and navigation shortcuts). Multiple mounting options allow for seamless integration within any rugged system.

### STANDARD FEATURES

- SDI Input (1), 3G/HD/SD
  - SMPTE 424M/292M/259M
- SDI Output (1), 3G/HD/SD
  - SMPTE 424M/292M/259M
- HDMI Input (1)
- DVI-I Input (1), Digital/Analog
- RS-170 Inputs (3)
- RS-170 Output (1)
- Picture-In-Picture (PIP), Picture-Over-Picture (POP)
- Up to 1080p60 High Definition Video
- MIL-C Power\*
- LED Backlight (1000:1 Dimming Ratio)
- Anti-Reflective and Anti-Glare Treatments
- Enhanced Sunlight Readability
- IP67/NEMA 6 Enclosure
- User Programmable Buttons (15), RS-232
- 7.0", 10.1", 13.3", 15.6" and 17.3" TFT AM LCD
- MIL-STD-461, 704, 810, 1275 Compliant

### OPTIONAL FEATURES

- Analog Resistive Touch Screen (USB or RS-232)
- Night Vision Compatible – Monochrome Red/Green
- NVIS MIL-STD-3009 Class B White Compliant



### MOUNT OPTIONS


(Quoted individually)



Panel



RAM



VESA



LCD SIZE	RESOLUTION	NITS	VIEWING ANGLE	CONTRAST RATIO	MAXIMUM POWER CONSUMPTION
7.0" TFT AM LCD	1920x1080	500	140° (H) x 120° (V)	600:1	30 Watts
10.1" TFT AM LCD	1920x1080	800	170° (H) x 170° (V)	800:1	35 Watts
13.3" TFT AM LCD	1920x1080	400	178° (H) x 178° (V)	800:1	35 Watts
15.6" TFT AM LCD	1920x1080	600	160° (H) x 145° (V)	800:1	35 Watts
17.3" TFT AM LCD	1920x1080	400	160° (H) x 140° (V)	600:1	40 Watts

#### TECHNICAL SPECIFICATIONS

Display	8-bit color, 16,777,216 colors
Dimming Ratio	1000:1
Video Inputs	SDI (1) 3G/HD/SD, HDMI (1), DVI-I (1) Digital/Analog, RS-170 (3)
Video Outputs	SDI (1) 3G/HD/SD, RS-170 (1)
Housing	Milled AL, Black Hard Anodized
Mount Options	Panel, RAM, VESA (75mm); Quoted individually.
Wide Range DC Power Input†	10-36 VDC (12, 24, 28 VDC nominal)
Power Conditioning	Protected against Internal Short Circuit, Load Dump, Over Voltage and Reverse Polarity

#### ENVIRONMENTAL SPECIFICATIONS

IP Rating	IP67 (NEMA 6 Submersible)
Operating Temperature	-46°C to 71°C (-51°F to 160°F); -20°C (-4°F) with Touch Option
Storage Temperature	-54°C to 71°C (-65°F to 160°F)
Humidity	0-100%
Altitude	

#### MILITARY SPECIFICATIONS

MIL-STD-461	EMI	MIL-STD-810	Method 512; Immersion
MIL-STD-704	Aircraft Power Requirements	MIL-STD-810	Method 513; Acceleration
MIL-STD-810	Method 500, Altitude	MIL-STD-810	Method 514; Procedure I, II, V, VI; General Vibration
MIL-STD-810	Method 501; I & II; High Temperature	MIL-STD-810	Method 516; Procedure I, Functional Shock
MIL-STD-810	Method 502; I & II; Low Temperature	MIL-STD-810	Method 520; Temp, Humidity, Vibe and Altitude
MIL-STD-810	Method 503; Temperature Shock	MIL-STD-1275	Vehicle Power Requirements
MIL-STD-810	Method 505; Solar Radiation	MIL-STD-1472	Thermal Contact Hazard
MIL-STD-810	Method 506; Rain	MIL-STD-3009	NVIS Compatible (Optional)
MIL-STD-810	Method 507; Humidity	MIL-PRF-22885	Sunlight Readability for Push Buttons
MIL-STD-810	Method 508; Fungus	MIL-A-8625	Standard Finish, Type III, Class 1 & 2
MIL-STD-810	Method 509; Salt/Fog	MIL-PRF-22750	Painted Finish, Optional, Minimum Quantity Required
MIL-STD-810	Method 510; Blowing Sand and Dust	MIL-DTL-26482	Connector, Qualified
MIL-STD-810	Method 511; Explosive Atmosphere	MIL-DTL-38999	Connector, Qualified

\* Cables not included

† Power range specified covers momentary environmental fluctuations generally found in a mobile environment while display is operating. For power initialization and continual operation, nominal voltages are required

**ON-GOING PRODUCT DEVELOPMENT MAY NECESSITATE DESIGN AND SPECIFICATION CHANGES WITHOUT NOTICE.**