

PTAC2

PROGRAMMABLE TACTICAL AWARENESS CONTROLLER SERIES

The PTAC2 highly ruggedized display offers Programmable Bezel Keys (ASCII or HEX code via RS-232 or RS-422 protocol) for control of external systems and/or internal display features. Multiple video and computer inputs (DVI-I, RS-170, VGA) and multiple mounting options allow for seamless integration within any rugged system.

STANDARD FEATURES

- User Programmable Bezel Keys (20), RS-232/RS-422 - Internal and/ or External Use
- Composite Video Inputs (4), PIP Capable
- Composite Video Output (1)
- Auto Sensing NTSC, PAL Formats
- DVI-I/VGA Inputs (2)
- SVGA Resolution (800x600)
- MIL-C Power*
- LED Backlight (3000:1 Dimming Ratio)
- Anti-Reflective and Anti-Glare Treatments
- Enhanced Sunlight Readability
- IP67/NEMA 6 Enclosure (Sealed Connectors*)
- 8.4", 10.4", 12.1" and 15.0" TFT AMLCD
- MIL-STD-461, 704, 810, 1275



* Cables not included

PROGRAMMABLE KEY INTERFACE FEATURES

- Integrated Bezel Key Assignment/Naming Capability
- Computer-based software available for integration of existing code

OPTIONAL FEATURES

- Resistive Touch Screen (USB or RS-232 Interface)
- XGA Display Resolution (1024x768)
- Night Vision Compatible – Monochrome Red/Green
- NVIS MIL-STD-3009 Class B White Compliant
- Remote Backlight Control (via Serial Command)

MOUNT OPTIONS

(Quoted individually)



Corner




Panel



RAM



Side



VESA



LCD SIZE	RESOLUTION	LUMINANCE	VIEWING ANGLE	CONTRAST RATIO	MAXIMUM POWER CONSUMPTION
8.4" TFT AMLCD	SVGA (800x600)	800 nits	160° (H) x 160° (V)	900:1	30 Watts
8.4" TFT AMLCD (Optional)	XGA (1024x768)	500 nits	160° (H) x 140° (V)	600:1	30 Watts
10.4" TFT AMLCD	SVGA (800x600)	800 nits	160° (H) x 160° (V)	900:1	30 Watts
10.4" TFT AMLCD (Optional)	XGA (1024x768)	1000 nits	160° (H) x 130° (V)	700:1	30 Watts
12.1" TFT AMLCD	SVGA (800x600)	550 nits	160° (H) x 140° (V)	600:1	30 Watts
12.1" TFT AMLCD (Optional)	XGA (1024x768)	1000 nits	190° (H) x 190° (V)	750:1	30 Watts
15.0" TFT AMLCD	XGA (1024x768)	800 nits	160° (H) x 140° (V)	800:1	40 Watts

TECHNICAL SPECIFICATIONS

Display	8-bit color, 16,777,216 colors. TFT AMLCD (Thin-Film Transistor Active-Matrix Liquid-Crystal Display)
Dimming Ratio	3000:1
Video Inputs	Composite Video (4), Auto Sensing NTSC, PAL-BGHID Formats; DVI-I/VGA (2)
Video Outputs	Composite Video (1)
Housing	Milled Aluminum, Black Hard Anodized
Mount Options	Corner, Panel, RAM, VESA (75mm), Side (12.1"-15.0" sizes); Quoted individually.
Wide Range DC Power Input†	10-36 VDC (12, 24, 28 VDC nominal)
Power Conditioning	Protected against Internal Short Circuit, Load Dump, Over Voltage and Reverse Polarity

ENVIRONMENTAL SPECIFICATIONS

IP Rating	IP67 (NEMA 6 Submersible)
Operating Temperature	-40°C to 71°C (-40°F to 160°F); (-20°C (-4°F) with Touch Option)
Storage Temperature	-51°C to 71°C (-60°F to 160°F)
Humidity	0-100%
Altitude	45,000 ft.

MILITARY SPECIFICATIONS

MIL-STD-461	EMI	MIL-STD-810	Method 512, Immersion
MIL-STD-704	Aircraft Power Requirements	MIL-STD-810	Method 512; Immersion
MIL-STD-810	Method 500; Altitude	MIL-STD-810	Method 513; Acceleration
MIL-STD-810	Method 501; I & II; High Temperature	MIL-STD-810	Method 514; Procedure I, II, V, VI; General Vibration
MIL-STD-810	Method 502; I & II; Low Temperature	MIL-STD-810	Method 516; Procedure I, Functional Shock
MIL-STD-810	Method 503; Temperature Shock	MIL-STD-810	Method 520; Temp, Humidity, Vibration, and Altitude
MIL-STD-810	Method 505; Solar Radiation	MIL-STD-1275	Vehicle Power Requirements
MIL-STD-810	Method 506; Rain	MIL-STD-1472	Thermal Contact Hazard
MIL-STD-810	Method 507; Humidity	MIL-STD-3009	NVIS Compatible (Optional)
MIL-STD-810	Method 508; Fungus	MIL-PRF-22885	Sunlight Readability for Push Buttons
MIL-STD-810	Method 509; Salt/Fog	MIL-A-8625	Standard Finish, Type III, Class 1 & 2
MIL-STD-810	Method 510; Blowing Sand and Dust	MIL-PRF-22750	Painted Finish, Optional, Minimum Quantity Required
MIL-STD-810	Method 511; Explosive Atmosphere	MIL-DTL-26842	(and 38999) Connector, Qualified

* - Cables not included.

† - Power range specified covers momentary environmental fluctuations generally found in a mobile environment while display is operating. For power initialization and continual operation, nominal voltages are required.

ON-GOING PRODUCT DEVELOPMENT MAY NECESSITATE DESIGN AND SPECIFICATION CHANGES WITHOUT NOTICE.

